

ALLEGRO CMOSIS CMV12000 12 MP



SPECIFICATIONS

Image Sensor Model	CMOSIS CMV12000
Sensor Format	4/3 inch
Max Resolution	4096 x 3072, 12MP
Max Frame Rate	32 fps (mono)
Burst Frame Rate	50 fps into internal buffer
Pixel Size	5.5 x 5.5 µm
Shutter	Global
Vision Standard	USB3 Vision™ Specification v1.0
Analog-to-Digital Converter	10-bit ADC
Sensor Video Data	10-bit digital data
Image Data Formats	YUV, YCbCr422/400, RGB8/565, processed Bayer8/10/12, Mono8/10/12/16, including packed
FPGA	Altera Cyclone V
On-Board Memory	256 MB
Dynamic Range	60 dB, Multi-slope programmable High Dynamic Range Mode
Partial Image Modes	2 x 2 Binning is supported. Programmable table based 256 ROI sequencing
Gain Control	Analog Gain & Digital Gain (programmable)
Shutter Speed	Manual / One-push modes, programmable via software, 0.03 ms to 1sec, longer exposure (integration) times can be supported if needed
Synchronization	via external trigger
Trigger Latency / Jitter	Latency TBD / Jitter +/- 0.5 microsecond (to be measured)
Interface Port	USB3
General Purpose I/O Port	12 Pin 7 mm Push-Pull Connector Programmable Opto-Isolated Trigger Input 2 Programmable Opto-Isolated Strobe Outputs
Power / Voltage	USB3 Host Port, 5 V +/- 10% at 0.9 A max
Dimensions (W x H x L)	57 x 57 x 64 mm (camera body)
Mass	321 g (without optics)
Lens Mount	F-Mount
Adjustable Back Focal Length	Optional
Emissions Compliance	CE, FCC, RoHS
Operating Temperature	-0° to 50° C
Storage Temperature	-30° to 70° C
Vibration Resistance	10 G (14 Hz to 200 Hz)
LED Indicator	Status and power monitoring Dual color
Enclosure	Pre-drilled mounting holes Tripod mount available Heavy duty aluminum Sealed Sensor Cavity
Warranty	4 years – Industry leading