



MODEL NUMBER	Clear Aperture	Isolation Minimum / Typical	Ins Loss Typical / Maximum	Transmission Minimum / Typical	Diameter	Length	Power Handling	Tunable	Broad-band
	mm	dB	dB	%					
390-460nm									
I-40-FR-2	2	30 / 35	0.5	89	1.0 / 25.4	1.0 / 25.4	300	N	N
I-40-2-M	2	35 / 40	0.6 / 0.8	83 / 86	1.0 / 25.4	2.32 / 59	100	N	N
I-40-2-H	2	35 / 40	0.6 / 0.8	83 / 86	1.0 / 25.4	2.91 / 74	250	N	N
I-40-FR-5	5	30 / 35	0.5	89	1.375 / 34.9	3.07 / 78	300	N	N
I-40-T-5-M	5	35 / 40	0.6 / 0.8	83 / 86	1.375 / 34.9	4.12 / 105	100	Y	N
I-40-T-5-H	5	35 / 40	0.6 / 0.8	83 / 86	1.375 / 34.9	5.01 / 127	250	Y	N
I-40-SD-5-M	5	53 / 55	1.5 / 2.0	63 / 79	1.375 / 34.9	4.12 / 105	100	Y	N
500-600nm									
I-56-FR-2	2	30 / 35	0.2	95	1.0 / 25.4	1.0 / 25.4	300	N	N
I-56-2-L	2	38 / 40	3	50	1.0 / 25.4	1.0 / 25.4	10	N	N
I-56-2-L-LH	2	38 / 40	3	50	1.0 / 25.4	2.4 / 61	10	N	N
I-56-2-M	2	38 / 40	0.5 / 0.7	85 / 89	1.0 / 25.4	2.32 / 59	100	N	N
I-56-2-M-LH	2	38 / 40	0.5 / 0.7	85 / 89	1.0 / 25.4	3.54 / 90	100	N	N
I-56-2-H	2	38 / 40	0.5 / 0.7	85 / 89	1.0 / 25.4	4.13 / 105	250	N	N
I-56-2-PBS	2	38 / 40	0.5 / 0.7	85 / 89	1.0 / 25.4	1.89 / 48	100	N	N
I-5060-C-2-L	2	35 / 38	3	50	1.0 / 25.4	2.40 / 61	10	N	Y
I-5060-C-2-M	2	35 / 38	0.5 / 0.7	85 / 89	1.0 / 25.4	3.54 / 90	100	N	Y
I-5060-C-2-H	2	35 / 38	0.5 / 0.7	85 / 89	1.0 / 25.4	4.13 / 105	250	N	Y
I-56-FR-5	5	30 / 35	0.2	95	1.375 / 34.9	2.54 / 64	300	N	N
I-56-T-5-L	5	38 / 40	3	50	1.375 / 34.9	2.54 / 64	10	Y	N
I-56-T-5-L-LH	5	38 / 40	3	50	1.375 / 34.9	4.12 / 105	10	Y	N
I-56-T-5-M	5	38 / 40	0.5 / 0.7	85 / 89	1.375 / 34.9	2.52 / 64	100	Y	N
I-56-T-5-M-LH	5	38 / 40	0.5 / 0.7	85 / 89	1.375 / 34.9	4.12 / 105	100	Y	N
I-56-T-5-H-LH	5	38 / 40	0.5 / 0.7	85 / 89	1.375 / 34.9	5.01 / 127	250	Y	N
I-5060-C-5-L	5	38 / 40	3	50	1.375 / 34.9	4.12 / 105	10	Y	Y
I-5060-C-5-M	5	38 / 40	0.6 / 0.75	84 / 86	1.375 / 34.9	4.12 / 105	100	Y	Y
I-5060-C-5-H	5	38 / 40	0.6 / 0.75	84 / 86	1.375 / 34.9	5.01 / 127	250	Y	Y
I-56-SD-5-L	5	50 / 55	4.5 / 5.0	30 / 35	1.375 / 34.9	4.12 / 105	10	Y	N
I-56-SD-5-M	5	55 / 60	1.0 / 1.5	70 / 79	1.375 / 34.9	4.12 / 105	100	Y	N
I-56-SD-5-H	5	55 / 60	1.0 / 1.5	70 / 79	1.375 / 34.9	5.01 / 127	250	Y	N
600-700nm									
I-633-FR-2	2	30 / 35	0.2	95	1.0 / 25.4	1.0 / 25.4	300	N	N
I-633-2-L	2	38 / 40	1.4/1.6	69/72	1.0 / 25.4	1.0 / 25.4	10	N	N
I-633-2-L-LH	2	38 / 40	1.4/1.6	69/72	1.0 / 25.4	2.40 / 61	10	N	N
I-633-2-M	2	38 / 40	0.5 / 0.7	85 / 89	1.0 / 25.4	2.32 / 59	100	N	N
I-633-2-M-LH	2	38 / 40	0.5 / 0.7	85 / 89	1.0 / 25.4	3.54 / 90	100	N	N
I-633-2-H	2	38 / 40	0.5 / 0.7	85 / 89	1.0 / 25.4	2.91 / 74	250	N	N
I-670-FR-2	2	30 / 35	0.2	95	1.0 / 25.4	1.0 / 25.4	300	N	N
I-670-2-L	2	38 / 40	1.4/1.6	69/72	1.0 / 25.4	1.0 / 25.4	10	N	N
I-670-2-L-LH	2	38 / 40	1.4/1.6	69/72	1.0 / 25.4	2.40 / 61	10	N	N
I-670-2-M	2	38 / 40	0.5 / 0.7	85 / 89	1.0 / 25.4	2.32 / 59	100	N	N
I-670-2-H	2	38 / 40	0.5 / 0.7	85 / 89	1.0 / 25.4	2.91 / 74	250	N	N
I-670-2-PBS	2	38 / 40	0.5 / 0.7	85 / 89	1.0 / 25.4	4.13 / 105	250	N	N
I-6070-C-2-L	2	35 / 38	1.4/1.6	69/72	1.0 / 25.4	2.40 / 61	10	N	Y
I-6070-C-2-M	2	35 / 38	0.5 / 0.75	84 / 89	1.0 / 25.4	3.54 / 90	100	N	Y
I-6070-C-2-H	2	35 / 38	0.5 / 0.75	84 / 89	1.0 / 25.4	4.13 / 105	250	N	Y
I-633-SD-2-PBS	2	35 / 38	0.5 / 0.75	84 / 89	1.0 / 25.4	4.13 / 105	250	N	N
I-67-FR-5	5	30 / 35	0.2	95	1.375 / 34.9	3.07 / 78	300	N	N
I-67-T-5-L	5	38 / 40	1.4/1.6	69/72	1.375 / 34.9	4.12 / 105	10	Y	N
I-67-T-5-M	5	38 / 40	0.5 / 0.7	85 / 89	1.375 / 34.9	4.12 / 105	100	Y	N
I-67-T-5-H	5	38 / 40	0.5 / 0.7	85 / 89	1.375 / 34.9	5.01 / 127	250	Y	N
I-6070-C-5-L	5	38 / 40	1.4/1.6	69/72	1.375 / 34.9	4.12 / 105	10	Y	Y
I-6070-C-5-M	5	38 / 40	0.5 / 0.75	84 / 89	1.375 / 34.9	4.12 / 105	100	Y	Y
I-6070-C-5-H	5	38 / 40	0.5 / 0.75	84 / 89	1.375 / 34.9	5.01 / 127	250	Y	Y
I-67-SD-5-L	5	50 / 55	1.8 / 2.3	56 / 66	1.375 / 34.9	4.12 / 105	10	Y	N
I-67-SD-5-M	5	55 / 60	1.0 / 1.5	70 / 79	1.375 / 34.9	4.12 / 105	100	Y	N
I-67-SD-5-H	5	55 / 60	1.0 / 1.5	70 / 79	1.375 / 34.9	5.01 / 127	250	Y	N

Specifications subject to change without notice

Isowave custom designs isolators to meet specific Performance, Package and Price requirements
 Medium ("M") and high ("H") power models are also available with PBS polarizers

Isowave - 64 Harding Avenue, Dover, NJ 07869, USA - Tel 973-328-7000 - Fax 973-328-7036 - Email: info@isowave.com



MODEL NUMBER	Clear Aperture	Isolation Minimum / Typical	Ins Loss Typical / Maximum	Transmission Minimum / Typical	Diameter	Length	Power Handling	Tunable	Broad-band
	mm	dB	dB	%	inch / mm	inch/mm	W/cm2	Yes/No	Yes/No
700-900nm			(see note)	(see note)			(see note)		
I-80-FR-2	2	30 / 35	0.2	95	1.0 / 25.4	2.40 / 61	300	N	N
I-80-2-L	2	38 / 40	0.5 / 0.8	83 / 89	1.0 / 25.4	2.40 / 61	50	N	N
I-80-2-M	2	38 / 40	0.4 / 0.7	85 / 91	1.0 / 25.4	3.54 / 90	100	N	N
I-80-2-H	2	38 / 40	0.4 / 0.7	85 / 91	1.0 / 25.4	4.13 / 105	250	N	N
I-7090-C-2-L	2	35 / 38	0.5 / 0.8	83 / 89	1.0 / 25.4	2.40 / 61	50	N	Y
I-7090-C-2-M	2	38 / 40	0.5 / 0.75	84 / 89	1.0 / 25.4	3.54 / 90	100	N	Y
I-7090-C-2-H	2	38 / 40	0.5 / 0.75	84 / 89	1.0 / 25.4	4.13 / 105	250	N	Y
I-80-U-2-L	2	60 / 63	0.9 / 1.4	72 / 81	1.0 / 25.4	3.31 / 84	50	N	N
I-80-FR-3	3	30 / 35	0.2	95	1.0 / 25.4	2.40 / 61	300	N	N
I-80-3-L	3	38 / 40	0.5 / 0.8	83 / 89	1.0 / 25.4	2.40 / 61	50	N	N
I-80-3-M	3	38 / 40	0.4 / 0.7	85 / 91	1.0 / 25.4	3.54 / 90	100	N	N
I-80-3-H	3	38 / 40	0.4 / 0.7	85 / 91	1.0 / 25.4	4.13 / 105	250	N	N
I-80-FR-4	4	30 / 35	0.2	95	1.375 / 34.9	3.07 / 78	300	N	N
I-80-T-4-L	4	38 / 40	0.5 / 0.8	83 / 89	1.375 / 34.9	3.03 / 77	50	Y	N
I-80-T-4-M	4	38 / 40	0.4 / 0.7	85 / 91	1.375 / 34.9	4.12 / 105	100	Y	N
I-80-T-4-H	4	38 / 40	0.4 / 0.7	85 / 91	1.375 / 34.9	5.01 / 127	250	Y	N
I-80-U-4-L	4	60 / 63	0.9 / 1.4	72 / 81	1.375 / 34.9	3.9 / 99	50	N	N
I-80-FR-5	5	30 / 35	0.2	95	1.375 / 34.9	3.07 / 78	300	N	N
I-80-T-5-L	5	38 / 40	0.5 / 0.8	83 / 89	1.375 / 34.9	4.12 / 105	50	Y	N
I-80-T-5-M	5	38 / 40	0.4 / 0.7	85 / 91	1.375 / 34.9	4.12 / 105	100	Y	N
I-80-T-5-PBS	5	38 / 40	0.4 / 0.7	85 / 91	1.375 / 34.9	3.07 / 78	100	Y	N
I-80-T-5-H	5	38 / 40	0.4 / 0.7	85 / 91	1.375 / 34.9	5.01 / 127	250	Y	N
I-7090-C-5-L	5	38 / 40	0.5 / 0.8	83 / 89	1.375 / 34.9	4.12 / 105	50	Y	Y
I-7090-C-5-M	5	38 / 40	0.5 / 0.75	84 / 89	1.375 / 34.9	4.12 / 105	100	Y	Y
I-7090-C-5-H	5	38 / 40	0.5 / 0.75	84 / 89	1.375 / 34.9	5.01 / 127	250	Y	Y
I-80-SD-4-M	4	55 / 60	1.0 / 1.5	70 / 79	1.375 / 34.9	4.69 / 119	100	Y	N
I-80-SD-4-MHM	4	55 / 60	1.0 / 1.5	70 / 79	1.375 / 34.9	4.69 / 119	100	Y	N
I-80-SD-4-H	4	55 / 60	1.0 / 1.5	70 / 79	1.375 / 34.9	4.97 / 127	250	Y	N
I-80-SD-5-L	5	55 / 60	1.0 / 1.5	70 / 79	1.375 / 34.9	4.69 / 119	50	Y	N
I-80-SD-5-M	5	55 / 60	1.0 / 1.5	70 / 79	1.375 / 34.9	4.69 / 119	100	Y	N
I-80-SD-5-MHM	5	55 / 60	1.0 / 1.5	70 / 79	1.375 / 34.9	4.69 / 119	100	Y	N
I-80-SD-5-H	5	55 / 60	1.0 / 1.5	70 / 79	1.375 / 34.9	4.97 / 127	250	Y	N
Note	At wavelengths below 780nm all Low Power models (suffix -L) have higher insertion loss, lower transmission and lower power handling capability								
900-1000nm									
I-92-T-4-L	4	35 / 38	0.3 / 0.5	89 / 93	1.375 / 34.9	4.0 / 102	50	Y	N
I-92-T-4-M	4	35 / 38	0.4 / 0.7	85 / 91	1.375 / 34.9	4.0 / 102	100	Y	N
I-92-T-4-H	4	35 / 38	0.4 / 0.7	85 / 91	1.375 / 34.9	5.01 / 127	250	Y	N
I-92-U-4-L	4	60 / 63	0.9 / 1.4	72 / 81	1.375 / 34.9	3.9 / 99	50	N	N
I-92-SD-4-M	4	55 / 60	1.0 / 1.5	70 / 79	1.375 / 34.9	4.69 / 119	100	Y	N
I-92-SD-5-M	5	55 / 60	1.0 / 1.5	70 / 79	1.375 / 34.9	4.69 / 119	100	Y	N
I-98-FR-2	2	30 / 35	0.2	95	1.0 / 25.4	2.40 / 61	300	N	N
I-98-2-L	2	35 / 38	0.3 / 0.5	89 / 93	1.0 / 25.4	2.40 / 61	50	N	N
I-98-2-M	2	35 / 38	0.4 / 0.7	85 / 91	1.0 / 25.4	3.54 / 90	100	N	N
I-98-2-H	2	35 / 38	0.4 / 0.7	85 / 91	1.0 / 25.4	4.13 / 105	250	N	N
I-9010-C-2-L	2	35 / 38	0.4 / 0.7	85 / 91	1.0 / 25.4	2.40 / 61	50	N	N
I-9010-C-2-M	2	38 / 40	0.5 / 0.7	85 / 89	1.0 / 25.4	3.54 / 90	100	N	N
I-9010-C-2-H	2	38 / 40	0.5 / 0.7	85 / 89	1.0 / 25.4	4.13 / 105	250	N	N
I-98-U-2-L	2	60 / 63	0.9 / 1.4	72 / 81	1.0 / 25.4	3.31 / 84	50	N	N
I-98-FR-4	4	30 / 35	0.2	95	1.375 / 34.9	3.0 / 76	300	N	N
I-98-T-4-L	4	35 / 38	0.3 / 0.5	89 / 93	1.375 / 34.9	4.0 / 102	50	Y	N
I-98-T-4-M	4	35 / 38	0.4 / 0.7	85 / 91	1.375 / 34.9	4.0 / 102	100	Y	N
I-98-T-4-H	4	35 / 38	0.4 / 0.7	85 / 91	1.375 / 34.9	5.01 / 127	250	Y	N
I-98-U-4-L	4	60 / 63	0.9 / 1.4	72 / 81	1.375 / 34.9	3.9 / 99	50	N	N
I-98-FR-5	5	30 / 35	0.2	95	1.375 / 34.9	3.0 / 76	300	N	N
I-98-T-5-L	5	35 / 38	0.3 / 0.5	89 / 93	1.375 / 34.9	4.0 / 102	50	Y	N
I-98-T-5-M	5	35 / 38	0.4 / 0.7	85 / 91	1.375 / 34.9	4.0 / 102	100	Y	N
I-98-T-5-H	5	35 / 38	0.4 / 0.7	85 / 91	1.375 / 34.9	5.01 / 127	250	Y	N
I-9010-C-5-L	5	35 / 38	0.6 / 0.75	84 / 86	1.375 / 34.9	4.0 / 102	50	Y	Y
I-9010-C-5-M	5	35 / 38	0.6 / 0.75	84 / 86	1.375 / 34.9	4.0 / 102	100	Y	Y
I-9010-C-5-H	5	35 / 38	0.6 / 0.75	84 / 86	1.375 / 34.9	5.01 / 127	250	Y	Y
I-98-SD-5-L	5	55 / 60	1.0 / 1.5	70 / 79	1.375 / 34.9	4.69 / 119	50	Y	N
I-98-SD-5-M	5	55 / 60	1.0 / 1.5	70 / 79	1.375 / 34.9	4.69 / 119	100	Y	N
I-98-SD-5-H	5	55 / 60	1.0 / 1.5	70 / 79	1.375 / 34.9	4.97 / 127	250	Y	N

Specifications subject to change without notice

Isowave custom designs isolators to meet specific Performance, Package and Price requirements
 Medium ("M") and high ("H") power models are also available with PBS polarizers



MODEL NUMBER	Clear Aperture	Isolation Minimum / Typical	Ins Loss Typical / Maximum	Transmission Minimum / Typical	Diameter	Length	Power Handling	Tunable	Broad-band
	mm	dB	dB	%	inch / mm	inch/mm	W/cm2	Yes/No	Yes/No
1000-1100									
I-106-FR-2	2	30 / 35	0.2	95	1.0 / 25.4	2.40 / 61	300	N	N
I-106-2-L	2	35 / 38	0.3 / 0.5	89 / 93	1.0 / 25.4	2.40 / 61	50	N	N
I-106-2-M	2	35 / 38	0.4 / 0.7	85 / 91	1.0 / 25.4	3.54 / 90	100	N	N
I-106-2-H	2	35 / 38	0.4 / 0.7	85 / 91	1.0 / 25.4	4.13 / 105	250	N	N
I-1011-C-2-L	2	35 / 38	0.4 / 0.7	85 / 91	1.0 / 25.4	2.40 / 61	50	N	Y
I-1011-C-2-M	2	38 / 40	0.5 / 0.7	85 / 89	1.0 / 25.4	3.54 / 90	100	N	Y
I-1011-C-2-H	2	38 / 40	0.5 / 0.7	85 / 89	1.0 / 25.4	4.13 / 105	250	N	Y
I-106-FR-3	3	30 / 35	0.2	95	1.0 / 25.4	2.40 / 61	300	N	N
I-106-3-L	3	35 / 38	0.3 / 0.5	89 / 93	1.0 / 25.4	2.40 / 61	50	N	N
I-106-3-M	3	35 / 38	0.4 / 0.7	85 / 91	1.0 / 25.4	3.84 / 98	100	N	N
I-106-3-H	3	35 / 38	0.4 / 0.7	85 / 91	1.0 / 25.4	4.43 / 113	250	N	N
I-106-FR-4	4	30 / 35	0.2	95	1.375 / 34.9	3.0 / 76	300	N	N
I-106-T-4-L	4	35 / 38	0.3 / 0.5	89 / 93	1.375 / 34.9	4.0 / 102	50	Y	N
I-106-T-4-M	4	35 / 38	0.4 / 0.7	85 / 91	1.375 / 34.9	4.0 / 102	100	Y	N
I-106-T-4-H	4	35 / 38	0.4 / 0.7	85 / 91	1.375 / 34.9	5.01 / 127	250	Y	N
I-106-FR-5	5	30 / 35	0.2	95	1.375 / 34.9	3.0 / 76	300	N	N
I-106-T-5-L	5	35 / 38	0.3 / 0.5	89 / 93	1.375 / 34.9	4.0 / 102	50	Y	N
I-106-T-5-M	5	35 / 38	0.4 / 0.7	85 / 91	1.375 / 34.9	4.0 / 102	100	Y	N
I-106-T-5-H	5	35 / 38	0.4 / 0.7	85 / 91	1.375 / 34.9	5.01 / 127	250	Y	N
I-1011-5-C-L	5	35 / 38	0.6 / 0.75	84 / 86	1.375 / 34.9	4.0 / 102	50	Y	Y
I-1011-5-C-M	5	35 / 38	0.6 / 0.75	84 / 86	1.375 / 34.9	4.0 / 102	100	Y	Y
I-1011-5-C-H	5	35 / 38	0.6 / 0.75	84 / 86	1.375 / 34.9	5.01 / 127	250	Y	Y
I-106-SD-5-L	5	55 / 60	1.0 / 1.5	70 / 79	1.375 / 34.9	5.09 / 130	50	N	N
I-106-SD-5-M	5	55 / 60	1.0 / 1.5	70 / 79	1.375 / 34.9	5.09 / 130	100	N	N
I-106-SD-5-H	5	55 / 60	1.0 / 1.5	70 / 79	1.375 / 34.9	5.39 / 137	250	N	N
I-106-FR-8	8	30 / 35	0.2	95	1.95 / 49.5	3.73 / 94.7	500	N	N
I-106-T-8-H-PBS	8	35 / 40	0.2 / 0.3	92 / 95	1.95 / 49.5	5.87 / 149.1	500	Y	N
I-1011-C-8-H	8	35 / 40	0.3 / 0.4	91 / 94	1.95 / 49.5	5.87 / 149.1	500	Y	Y
1100-1200									
I-116-5-FR	5	30 / 35	0.3	93	1.375 / 34.9	3.0 / 76	300	N	N
I-116-T-5-L	5	35 / 38	0.4 / 0.7	85 / 91	1.375 / 34.9	5.12 / 130	50	Y	N
I-116-T-5-M	5	35 / 38	0.5 / 0.8	85 / 91	1.375 / 34.9	5.12 / 130	100	Y	N
I-116-T-5-H	5	35 / 38	0.4 / 0.7	85 / 91	1.375 / 34.9	6.34 / 161	250	Y	N

Specifications subject to change without notice

Isowave custom designs isolators to meet specific Performance, Package and Price requirements
 Medium ("M") and high ("H") power models are also available with PBS polarizers

Isowave - 64 Harding Avenue, Dover, NJ 07869, USA - Tel 973-328-7000 - Fax 973-328-7036 - Email: info@isowave.com

MODEL NUMBER	Clear Aperture	Isolation Minimum / Typical	Ins Loss Typical / Maximum	Transmission Minimum / Typical	Diameter	Length	Power Handling	Tunable	Broad-band
	mm	dB	dB	%	inch / mm	inch/mm	W/cm2	Yes/No	Yes/No
LPE Film Based									
I-80-B-4-L	4	30 / 35	3 to 6	25 to 50	0.75 / 19	1.48 / 37.6	10	Y	N
I-106-B-FR-4	4	30	1	80	0.75 / 19	1.48 / 37.6	10	N	N
I-106-B-4-L	4	30 / 35	1.2 / 1.5	70 / 75	0.75 / 19	1.48 / 37.6	10	Y	N
I-11-B-FR-4	4	30	0.3	93	0.75 / 19	1.48 / 37.6	100	N	N
I-11-B-4-L	4	30 / 35	0.4 / 0.6	87 / 91	0.75 / 19	1.48 / 37.6	100	Y	N
I-11-B-FR-5	5	30	0.3	93	0.75 / 19	1.48 / 37.6	100	N	N
I-11-B-5-L	5	30 / 35	0.4 / 0.6	87 / 91	0.75 / 19	1.48 / 37.6	100	Y	N
I-11-T-5-H	5	30 / 35	0.6 / 0.75	87 / 84	1.375 / 34.9	4.92 / 125	100	Y	N
I-12-B-FR-4	4	30	0.1	97	0.75 / 19	1.48 / 37.6	100	N	N
I-12-B-4-L	4	35 / 40	0.2 / 0.4	91 / 95	0.75 / 19	1.48 / 37.6	100	Y	N
I-12-B-FR-5	5	30	0.1	97	0.75 / 19	1.48 / 37.6	100	N	N
I-12-B-5-L	5	35 / 40	0.2 / 0.4	91 / 95	0.75 / 19	1.48 / 37.6	100	Y	N
I-12-T-5-H	5	35 / 40	0.5 / 0.7	85 / 89	1.375 / 34.9	4.92 / 125	100	Y	N
I-13-B-FR-4	4	35	0.1	97	0.75 / 19	1.48 / 37.6	300	N	N
I-13-B-4-L	4	38 / 43	0.2 / 0.4	91 / 95	0.75 / 19	1.48 / 37.6	300	Y	N
I-13-T-4-H	4	35 / 38	0.5 / 0.7	85 / 89	1.375 / 34.9	4.92 / 125	300	Y	N
I-13-B-FR-5	5	35	0.1	97	0.75 / 19	1.48 / 37.6	300	N	N
I-13-B-5-L	5	38 / 43	0.2 / 0.4	91 / 95	0.75 / 19	1.48 / 37.6	300	Y	N
I-14-B-FR-4	4	35	0.1	97	0.75 / 19	1.48 / 37.6	300	N	N
I-14-B-4-L	4	38 / 43	0.2 / 0.4	91 / 95	0.75 / 19	1.48 / 37.6	300	Y	N
I-15-B-FR-4	4	35	0.1	97	0.75 / 19	1.48 / 37.6	300	N	N
I-15-B-4-L	4	38 / 43	0.2 / 0.4	91 / 95	0.75 / 19	1.48 / 37.6	300	Y	N
I-15-B-FR-5	5	35	0.1	97	0.75 / 19	1.48 / 37.6	300	N	N
I-15-B-5-L	5	38 / 43	0.2 / 0.4	91 / 95	0.75 / 19	1.48 / 37.6	300	Y	N
I-15-T-5-H	5	35 / 38	0.5 / 0.7	85 / 89	1.375 / 34.9	4.92 / 125	300	Y	N
I-16-B-FR-4	4	35	0.1	97	0.75 / 19	1.48 / 37.6	300	N	N
I-16-B-4-L	4	38 / 43	0.2 / 0.4	91 / 95	0.75 / 19	1.48 / 37.6	300	Y	N
I-17-B-FR-4	4	28	0.25	97	0.75 / 19	1.48 / 37.6	50	N	N
I-17-B-4-L	4	30 / 35	0.4 / 0.6	86 / 91	0.75 / 19	1.48 / 37.6	50	Y	N
I-21-B-FR-4	4	28	0.5	89	0.75 / 19	1.48 / 37.6	25	N	N
I-21-B-4-L	4	30 / 35	0.8 / 1	79 / 83	0.75 / 19	1.48 / 37.6	25	Y	N
I-21-B-FR-5	5	28	0.5	89	0.75 / 19	1.48 / 37.6	25	N	N
I-21-B-5-L	5	30 / 35	0.8 / 1	79 / 83	0.75 / 19	1.48 / 37.6	25	Y	N
I-23-B-FR-4	5	28	0.5	89	0.75 / 19	1.48 / 37.6	25	N	N
I-23-B-4-L	5	30 / 35	0.8 / 1	79 / 83	0.75 / 19	1.48 / 37.6	25	Y	N
I-23-B-FR-5	5	28	0.5	89	0.75 / 19	1.48 / 37.6	25	N	N
I-23-B-5-L	5	30 / 35	0.8 / 1	79 / 83	0.75 / 19	1.48 / 37.6	25	Y	N
LPE Film Based - Double Stage									
I-12-UHP-4 or 5	4 or 5	60 / 65	0.5 / 1.0	79 / 89	0.75 / 19	1.67 / 42.3	300	N	N
I-13-UHP-4 or 5	4 or 5	63 / 75	0.4 / 0.8	83 / 91	0.75 / 19	1.67 / 42.3	300	N	N
I-14-UHP-4 or 5	4 or 5	63 / 75	0.4 / 0.8	83 / 91	0.75 / 19	1.67 / 42.3	300	N	N
I-15-UHP-4 or 5	4 or 5	63 / 75	0.4 / 0.8	83 / 91	0.75 / 19	1.67 / 42.3	300	N	N
I-16-UHP-4 or 5	4 or 5	63 / 75	0.4 / 0.8	83 / 91	0.75 / 19	1.67 / 42.3	300	N	N
I-17-UHP-4 or 5	4 or 5	63 / 75	0.4 / 0.8	83 / 91	0.75 / 19	1.67 / 42.3	50	N	N
I-21-UHP-4 or 5	4 or 5	63 / 75	1.5 / 2	63 / 70	0.75 / 19	1.67 / 42.3	25	N	N
I-23-UHP-4 or 5	4 or 5	63 / 75	1.5 / 2	63 / 70	0.75 / 19	1.67 / 42.3	25	N	N

Specifications subject to change without notice

Isowave custom designs isolators to meet specific Performance, Package and Price requirements

Medium ("M") and high ("H") power models are also available with PBS polarizers

Isowave - 64 Harding Avenue, Dover, NJ 07869, USA - Tel 973-328-7000 - Fax 973-328-7036 - Email: info@isowave.com